

Attachment 2 Environmental resistance

1. Operating temperature range : 5 to 30°C (QT: -10 to 45°C)
2. Ground storage temperature: 0±10°C
3. Mechanical environments (Vibration)

•Sinusoidal vibration

Frequency range	Acceleration level
5 to 27.9 Hz	6.4 mm (Single Amplitude)
27.9 to 100 Hz	196 m/s ² (20 g)

•Random vibration

Frequency range	Acceleration density	Grms
20 to 58 Hz	+6 dB/oct	23.63 (231.57 m/s ² rms)
58 to 700 Hz	48.02 m ² /s ³ (0.5 g ² / Hz)	
700 to 2000 Hz	-6 dB/oct	

Setup condition : > SOC(State of Charge)80%, cell is pressed using flat plates by 0.211±0.015MPa

4. Mechanical environments(Shock)

Frequency range	Acceleration density
200 Hz	392 m/s ² (40 g)
200 to 2000 Hz	+9.296 d/B/octave
2000 to 7000 Hz	13,720 m/s ² (1400 g)

Setup condition : > SOC65%, cell is pressed using flat plates by 0.211±0.015MPa

5. Mechanical environments(Acceleration)

Level	Period
245 m/s ² (25 g)	5 minutes

Setup condition : > SOC80%, cell is pressed using flat plates by 0.211±0.015MPa

6. Radiation resistance characteristics: N/A